



Canon Ultra Wide Angle Zoom Lenses



Canon Standard Zoom Lenses



Canon Telephoto Zoom Lenses



Canon EF 8-15mm f/4L Fisheye USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 180°~ 175°30'
- * Lens Construction: 14 Elements in 11 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : 22
- * Filter Diameter (mm) : Gelatin
- * Length x Max. Diameter (mm) : 83 x 78.5
- * Weight (g) : 540



600336 Ultra Wide Angle Zoom LensUS\$ 1,803.20

Canon EF 24-70mm f/4L IS USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 84°~ 34°
- * Lens Construction: 15 Elements in 12 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 22
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 93 x 83.4
- * Weight (g) : 600



600656 Standard Zoom LensAsk

Canon EF 70-300mm f/4-5.6 IS II USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 34°~ 8°15'
- * Lens Construction: 17 Elements in 12 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : f/32-45
- * Filter Diameter (mm) : 67 mm
- * Length x Max. Diameter (mm) : 145.5 x 80
- * Weight (g) : 710



603275 Telephoto Zoom LensUS\$ 771.00

Canon EF 16-35mm f/2.8L III USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 108°10'~ 63°
- * Lens Construction: 16 Elements in 11 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 22
- * Filter Diameter (mm) : 82mm
- * Length x Max. Diameter (mm) : 127.5 x 88.5
- * Weight (g) : 790



600337 Ultra Wide Angle Zoom Lens.....US\$ 2,900.00

Canon EF 24-70mm f/2.8L II USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 84°~ 34°
- * Lens Construction: 18 Elements in 13 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 22
- * Filter Diameter (mm) : 82 mm
- * Length x Max. Diameter (mm) : 113 x 88.5
- * Weight (g) : 805



600661 Standard Zoom Lens US\$ 2,254.80

Canon EF 70-200mm f/4L IS II USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 34°~ 12°
- * Lens Construction: 20 Elements in 15 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : f/32
- * Filter Diameter (mm) : 72 mm
- * Length x Max. Diameter (mm) : 176 x 80
- * Weight (g) : 780



603249 Telephoto Zoom LensUS\$ 1,996.80

Canon EF 16-35mm f/4L IS USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 108°10'~ 63°
- * Lens Construction: 16 Elements in 12 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 22
- * Filter Diameter (mm) : 77mm
- * Length x Max. Diameter (mm) : 112.8 x 82.6
- * Weight (g) : 615



600338 Ultra Wide Angle Zoom LensUS\$ 1,722.60

Canon EF 24-105mm f/4L IS II USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 84°~ 23°20'
- * Lens Construction: 17 Elements in 12 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 10
- * Minimum Aperture : 22
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 118 x 83.5
- * Weight (g) : 795



600662 Standard Zoom Lens US\$ 1,722.60

Canon EF 70-200mm f/2.8L IS III USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 34°~ 12°
- * Lens Construction: 23 Elements in 19 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : f/32
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 199 x 88.8
- * Weight (g) : 1480



603251 Telephoto Zoom LensUS\$ 2,835.50

Canon EF 11-24mm f/4L USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 126°05'~ 84°
- * Lens Construction: 11 Elements in 16 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : f/22
- * Filter Diameter (mm) : Rear Gelatin Filter Holder
- * Length x Max. Diameter (mm) : 132 x 108
- * Weight (g) : 1180



600339 Ultra Wide Angle Zoom LensUS\$ 3,609.50

Canon EF 24-105mm f/3.5-5.6 IS STM

- * EF Mount Lens
- * Angle of View (Diagonal) : 84°~ 23°20'
- * Lens Construction: 17 Elements in 13 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : f/22-36
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 104 x 83.4
- * Weight (g) : 525



600663 Standard Zoom Lens.....Ask

Canon EF 28-300mm f/3.5-5.6L IS USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 75°~ 8°15'
- * Lens Construction: 23 Elements in 19 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : 22-40
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 1184 x 92
- * Weight (g) : 1670



603243 Telephoto Zoom LensEoL

Canon EF 17-40mm f/4L USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 104°~ 57°30'
- * Lens Construction: 12 Elements in 9 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : 22
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 96.8 x 83.5
- * Weight (g) : 475



600340 Ultra Wide Angle Zoom LensAsk

Canon Macro Lenses



Canon EF 70-300mm f/4-5.6L IS USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 34°~ 8°15'
- * Lens Construction: 19 Elements in 14 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : 32-45
- * Filter Diameter (mm) : 67 mm
- * Length x Max. Diameter (mm) : 143 x 89
- * Weight (g) : 1050



603273 Telephoto Zoom LensAsk

Canon EF 100mm f/2.8 Macro USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 24°
- * Lens Construction: 12 Elements in 8 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : 32
- * Filter Diameter (mm) : 58 mm
- * Length x Max. Diameter (mm) : 118.6 x 78.6
- * Weight (g) : 580



603372 Macro Lens Ask

Canon MP-E 65mm f/2.8 1-5X Macro Photo

- * Manual Focus Macro Lens for EOS Cameras
- * Angle of View (Diagonal) : 18°40'
- * Lens Construction: 10 Elements in 8 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : -
- * Minimum Aperture : 6
- * Filter Diameter (mm) : 58 mm
- * Length x Max. Diameter (mm) : 98 x 81
- * Weight (g) : 710



603371 Macro LensAsk

Canon EF 100-400mm f/4.5-5.6L IS II USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 24°~ 6°10'
- * Lens Construction: 19 Elements in 14 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : 32-40
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 193 x 94
- * Weight (g) : 1640



603347 Telephoto Zoom LensUS\$ 3,190.30

Canon EF 100mm f/2.8L Macro IS USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 24°
- * Lens Construction: 15 Elements in 12 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 32
- * Filter Diameter (mm) : 67 mm
- * Length x Max. Diameter (mm) : 123 x 77.7
- * Weight (g) : 625



603373 Macro LensUS\$ 1,464.50

Canon EF 180mm f/3.5L Macro USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 13°40'
- * Lens Construction: 14 Elements in 12 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : 32
- * Filter Diameter (mm) : 72 mm
- * Length x Max. Diameter (mm) : 186.6 x 82.5
- * Weight (g) : 1090



603374 Macro LensAsk

Canon EF 200-400mm f/4L IS USM Extender 1.4x

- * EF Mount Lens
- * Angle of View (Diagonal) : 12°~ 6°10'
- * Lens Construction: 25 Elements in 20 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 32
- * Filter Diameter (mm) : 52 mm (Drop-in)
- * Length x Max. Diameter (mm) : 366 x 128
- * Weight (g) : 3620



603348 Telephoto Zoom LensUS\$16,319.40



Canon Wide Angle Lenses

Canon Telephoto Lenses

Canon Standard & Medium Lenses

Canon Wide Angle Lenses



Canon Telephoto Lenses



Canon Standard and Medium Lenses



Canon EF 14mm f/2.8 II USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 114°
- * Lens Construction: 14 Elements in 11 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 6
- * Minimum Aperture : 22
- * Filter Diameter (mm) : Gelatin
- * Length x Max. Diameter (mm) : 94 x 80
- * Weight (g) : 645



603350 Wide Angle Lens.....Ask

Canon EF 135mm f/2L USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 18°
- * Lens Construction: 10 Elements in 8 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : 32
- * Filter Diameter (mm) : 72 mm
- * Length x Max. Diameter (mm) : 112 x 82.5
- * Weight (g) : 750



603361 Telephoto LensAsk

Canon EF 40mm f/2.8 STM

- * EF Mount Lens
- * Angle of View (Diagonal) : 57°30'
- * Lens Construction: 6 Elements in 4 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : 22
- * Filter Diameter (mm) : 52 mm
- * Length x Max. Diameter (mm) : 22.8 x 68.2
- * Weight (g) : 130



603404 Standard LensAsk

Canon EF 24mm f/1.4 II USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 84°
- * Lens Construction: 13 Elements in 10 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : 22
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 86.9 x 83.5
- * Weight (g) : 650



603354 Wide Angle Lens.....Ask

Canon EF 200mm f/2L IS USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 12°
- * Lens Construction: 17 Elements in 12 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : 32
- * Filter Diameter (mm) : 52mm (Drop-in)
- * Length x Max. Diameter (mm) : 208 x 128
- * Weight (g) : 2520



603363 Telephoto LensAsk

Canon EF 50mm f/1.2 L USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 46°
- * Lens Construction: 8 Elements in 6 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : 16
- * Filter Diameter (mm) : 72 mm
- * Length x Max. Diameter (mm) : 65.5 x 85.8
- * Weight (g) : 590



603391 Standard LensUS\$ 2,029.00

Canon EF 24mm f/2.8 IS USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 84°
- * Lens Construction: 11 Elements in 9 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : 22
- * Filter Diameter (mm) : 58 mm
- * Length x Max. Diameter (mm) : 55.7 x 68.4
- * Weight (g) : 280



603355 Wide Angle Lens.....Ask

Canon EF 300mm f/2.8L IS II USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 8°15'
- * Lens Construction: 16 Elements in 12 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 32
- * Filter Diameter (mm) : 52mm (Drop-in)
- * Length x Max. Diameter (mm) : 248 x 128
- * Weight (g) : 2350



603365 Telephoto LensAsk

Canon EF 50mm f/1.4 USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 46°
- * Lens Construction: 6 Elements in 6 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : 22
- * Filter Diameter (mm) : 58 mm
- * Length x Max. Diameter (mm) : 50.5 x 73.8
- * Weight (g) : 290



603392 Standard LensUS\$ 529.90

Canon EF 28mm f/2.8 IS USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 75°
- * Lens Construction: 9 Elements in 7 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : 22
- * Filter Diameter (mm) : 58 mm
- * Length x Max. Diameter (mm) : 51.5 x 68.4
- * Weight (g) : 260



603359 Wide Angle Lens.....Ask

Canon EF 300mm f/4L IS USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 8°15'
- * Lens Construction: 15 Elements in 11 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : 32
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 221 x 90
- * Weight (g) : 1190



603366 Telephoto LensAsk

Canon EF 50mm f/1.8 STM

- * EF Mount Lens
- * Angle of View (Diagonal) : 46°
- * Lens Construction: 6 Elements in 5 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : f/22
- * Filter Diameter (mm) : 49 mm
- * Length x Max. Diameter (mm) : 39.3 x 69.2
- * Weight (g) : 216



603397 Standard LensUS\$ 185.80

Canon EF 35mm f/1.4 II USM

- * EF Mount L-Series Lens/Full-Frame Format
- * Aperture Range: f/1.4-22
- * Blue Spectrum Refractive Optics
- * Two Aspherical Elements, One UD Element
- * Subwavelength and Fluorine Coatings
- * Ultrasonic Autofocus Motor
- * Full-Time Manual Focus Override
- * Weather-Sealed Design
- * Rounded 9-Blade Diaphragm



603357 Wide Angle Lens.....US\$ 2,658.10

Canon EF 400mm f/2.8L IS III USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 6°10'
- * Lens Construction: 17 Elements in 13 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 32
- * Filter Diameter (mm) : 52mm (Drop-in)
- * Length x Max. Diameter (mm) : 343 x 163
- * Weight (g) : 2840



603383 Super Telephoto Lens.....US\$ 14,262.40

Canon EF 85mm f/1.2L II USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 28°30'
- * Lens Construction: 8 Elements in 7 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : 16
- * Filter Diameter (mm) : 72 mm
- * Length x Max. Diameter (mm) : 84 x 91.5
- * Weight (g) : 1025



603394 Standard LensAsk

Canon EF 35mm f/2 IS USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 63°
- * Lens Construction: 10 Elements in 8 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : 22
- * Filter Diameter (mm) : 67 mm
- * Length x Max. Diameter (mm) : 62.6 x 77.9
- * Weight (g) : 335



603358 Wide Angle Lens.....Ask

Canon EF 400mm f/4 DO IS II USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 6°10'
- * Lens Construction: 18 Elements in 12 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 32
- * Filter Diameter (mm) : 52mm (Drop-in)
- * Length x Max. Diameter (mm) : 232.7 x 128
- * Weight (g) : 2100



603384 Super Telephoto Lens.....Ask

Canon EF 85mm f/1.4L IS USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 28°30'
- * Lens Construction: 14 Elements in 10 Group
- * Fluorine Coating : support
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : f/22
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 105.4 x 88.6
- * Weight (g) : 950



603398 Standard LensUS\$ 2,125.80

Canon EF 600mm f/4L IS III USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 4°10'
- * Lens Construction: 17 Elements in 13 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 32
- * Filter Diameter (mm) : 52mm (Drop-in)
- * Length x Max. Diameter (mm) : 448 x 168
- * Weight (g) : 3050



603387 Super Telephoto Lens.....US\$ 17,319.40

Canon EF 500mm f/4L IS II USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 5°
- * Lens Construction: 16 Elements in 12 Group
- * Fluorine Coating : Yes
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 32
- * Filter Diameter (mm) : 52mm (Drop-in)
- * Length x Max. Diameter (mm) : 383 x 146
- * Weight (g) : 3190



603386 Super Telephoto Lens.....Ask

Canon EF 85mm f/1.8 USM

- * EF Mount Lens
- * Angle of View (Diagonal) : 28°30'
- * Lens Construction: 9 Elements in 7 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : 22
- * Filter Diameter (mm) : 58 mm
- * Length x Max. Diameter (mm) : 71.5 x 75
- * Weight (g) : 425



603395 Standard LensUS\$ 706.50



Canon EF-S Lenses

Canon EF-S Lenses

Canon TS-E & MP-E Lenses

Canon EF-S Lenses



Canon TS-E Lenses (Tilt-Shift)



Canon EF-S 24mm f/2.8 STM

- * EF-S Mount Lens
- * Angle of View (Diagonal) : 59°10'
- * Lens Construction: 6 Elements in 5 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : f/22
- * Filter Diameter (mm) : 52 mm
- * Length x Max. Diameter (mm) : 22.8 x 68.2
- * Weight (g) : 125



603410 EF-S Lens.....US\$ 220.20

Canon EF-S 18-55mm f/4-5.6 IS STM

- * EF-S Mount Lens
- * Angle of View (Diagonal) : 74°20' - 27°50'
- * Lens Construction: 12 Elements in 10 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : 22-32
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 58 mm
- * Length x Max. Diameter (mm) : 61.8 x 66.5
- * Weight (g) : 215



600350 EF-S Lens.....US\$ 337.20

Canon TS-E 17mm f/4L

- * Tilt-Shift L-Series Manual Focus Lens
- * Angle of View (Diagonal) : 104°
- * Lens Construction: 18 Elements in 12 Group
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : 22
- * Image Stabilizer Mode : -
- * Filter Diameter (mm) : -
- * Length x Max. Diameter (mm) : 106.7 x 88.9
- * Weight (g) : 820



603377 Tilt-Shift LensUS\$ 3,058.90

Canon EF-S 35mm f/2.8 Macro IS STM

- * EF-S Mount Lens
- * Angle of View (Diagonal) : 42°35'
- * Lens Construction: 10 Elements in 6 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : f/32
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 49 mm
- * Length x Max. Diameter (mm) : 55.8 x 69.2
- * Weight (g) : 190



603244 EF-S Lens.....US\$ Ask

Canon EF-S 18-135mm f/3.5-5.6 IS USM

- * EF-S Mount Lens
- * Angle of View (Diagonal) : 74°20' - 11°30'
- * Lens Construction: 16 Elements in 12 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : 22-36
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 67 mm
- * Length x Max. Diameter (mm) : 96 x 77.4
- * Weight (g) : 515



600352 EF-S Lens.....US\$ 839.60

Canon TS-E 24mm f/3.5L II

- * Tilt-Shift L-Series Manual Focus Lens
- * Angle of View (Diagonal) : 84°
- * Lens Construction: 16 Elements in 11 Group
- * No. of Diaphragm Blades : 8
- * Minimum Aperture : 22
- * Image Stabilizer Mode : -
- * Filter Diameter (mm) : 82 mm
- * Length x Max. Diameter (mm) : 106.9 x 88.5
- * Weight (g) : 780



603378 Tilt-Shift LensUS\$ 2,714.80

Canon EF-S 60mm f/2.8 Macro USM

- * EF-S Mount Lens
- * Angle of View (Diagonal) : 24°30'
- * Lens Construction: 12 Elements in 8 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : 32
- * Filter Diameter (mm) : 52 mm
- * Length x Max. Diameter (mm) : 69.8 x 73
- * Weight (g) : 335



603411 EF-S Lens.....US\$ Ask

Canon EF-S 18-135mm f/3.5-5.6 IS STM

- * EF-S Mount Lens
- * Angle of View (Diagonal) : 74°20' - 11°30'
- * Lens Construction: 16 Elements in 12 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : 22-36
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 67 mm
- * Length x Max. Diameter (mm) : 96 x 76.6
- * Weight (g) : 480



600353 EF-S Lens.....No Longer Available

Canon TS-E 50mm f/2.8 Marco

- * Tilt-Shift L-Series Manual Focus Lens
- * Angle of View (Diagonal) : 46°
- * Lens Construction: 12 Elements in 9 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : f/32
- * Image Stabilizer Mode : -
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 114.9 x 86.9
- * Weight (g) : 945



603379 Tilt-Shift LensUS\$ 3,127.70

Canon EF-S 10-18mm f/4.5-5.6 IS STM

- * EF-S Mount Lens
- * Angle of View (Diagonal) : 107°30' - 74°20'
- * Lens Construction: 14 Elements in 11 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : f/22-29
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 67 mm
- * Length x Max. Diameter (mm) : 72.0 x 74.6
- * Weight (g) : 240



603412 EF-S Lens.....US\$ 426.70

Canon EF-S 18-200mm f/3.5-5.6 IS

- * EF-S Mount Lens
- * Angle of View (Diagonal) : 74°20' - 7°50'
- * Lens Construction: 16 Elements in 12 Group
- * No. of Diaphragm Blades : 6
- * Minimum Aperture : 22-36
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 72 mm
- * Length x Max. Diameter (mm) : 102 x 78.6
- * Weight (g) : 595



603414 EF-S Lens.....No Longer Available

Canon TS-E 90mm f/2.8 Marco

- * Tilt-Shift L-Series Manual Focus Lens
- * Angle of View (Diagonal) : 27°
- * Lens Construction: 12 Elements in 9 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : f/45
- * Image Stabilizer Mode : -
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 116.5 x 86.9
- * Weight (g) : 915



603380 Tilt-Shift LensUS\$ 3,127.70

Canon EF-S 10-22mm f/3.5-4.5 USM

- * EF-S Mount Lens
- * Angle of View (Diagonal) : 107°30' - 63°30'
- * Lens Construction: 13 Elements in 10 Group
- * No. of Diaphragm Blades : 6
- * Minimum Aperture : 22-29
- * Fluorine Coating : -
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 89.8 x 83.5
- * Weight (g) : 385



603413 EF-S Lens.....US\$ 925.60

Canon EF-S 17-55mm f/2.8 IS USM

- * EF-S Mount Lens
- * Angle of View (Diagonal) : 78°30' - 27°50'
- * Lens Construction: 19 Elements in 12 Group
- * Fluorine Coating : -
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : 22
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 110.6 x 83.5
- * Weight (g) : 645



600345 EF-S Lens.....No Longer Available

Canon EF-S 55-250mm f/4-5.6 IS STM

- * EF-S Mount Lens
- * Angle of View (Diagonal) : 27°50' - 6°15'
- * Lens Construction: 15 Elements in 12 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : f/22-32
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 58 mm
- * Length x Max. Diameter (mm) : 111.2 x 70
- * Weight (g) : 375



603345 EF-S Lens.....No Longer Available

Canon TS-E 135mm f/4L Marco

- * Tilt-Shift L-Series Manual Focus Lens
- * Angle of View (Diagonal) : 18°
- * Lens Construction: 11 Elements in 7 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : f/45
- * Image Stabilizer Mode : -
- * Filter Diameter (mm) : 82 mm
- * Length x Max. Diameter (mm) : 139.1 x 88.5
- * Weight (g) : 1,110



603381 Tilt-Shift LensUS\$ 3,127.70

Canon MP-E 65mm f/2.8 1-5X Macro Photo

- * EF Mount Lens
- * Angle of View (Diagonal) : 18°40'
- * Lens Construction: 10 Elements in 8 Group
- * No. of Diaphragm Blades : -
- * Minimum Aperture : 6
- * Image Stabilizer Mode : -
- * Filter Diameter (mm) : 58 mm
- * Length x Max. Diameter (mm) : 98 x 81
- * Weight (g) : 710



603381 Macro LensNo Longer Available



Canon

RF LENSES

EOS R SYSTEM EOS R CAMERA EOS RP CAMERA RF LENSES



Canon RF Lenses



Canon RF Lenses

RF Lens



Canon RF24-70mm f/2.8L IS USM

- * RF Mount for EOS R series mirrorless cameras
- * Angle of View (Diagonal) : 84° ~ 34°00'
- * Lens Construction: 21 Elements in 15 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 22
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 82 mm
- * Length x Max. Diameter (mm) : 125.7 x (Auto)88.5
- * Weight (g) : 900



617491 RF LensUS\$ 3,923.00

Canon RF28-70mm f/2L USM

- * RF Mount for EOS R series mirrorless cameras
- * Angle of View (Diagonal) : 65° ~ 29°00'
- * Lens Construction: 19 Elements in 13 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 22
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 95 mm
- * Length x Max. Diameter (mm) : 139.8 x 103.8
- * Weight (g) : 1430



617492 RF LensUS\$ 4,590.10

Canon RF24-105mm f/4L IS USM

- * RF Mount for EOS R series mirrorless cameras
- * Angle of View (Diagonal) : 84° ~ 23°20'
- * Lens Construction: 18 Elements in 14 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 22
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 107.3 x 83.5
- * Weight (g) : 700



617490 RF LensUS\$ 1,957.80

Canon RF24-105mm f/4-7.1 IS STM

- * RF Mount
- * Angle of View (Diagonal) : 84°00'~23°20'
- * Lens Construction: 13 Elements in 11 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : 22
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 67 mm
- * Length x Max. Diameter (mm) : 88.8 x 76.6
- * Weight (g) : 395



617489 RF LensUS\$ 667.50

Canon RF70-200mm f/2.8L IS USM

- * RF Mount for EOS R series mirrorless cameras
- * Angle of View (Diagonal) : 34° ~ 12°
- * Lens Construction: 17 Elements in 13 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 32
- * Image Stabilizer Mode : Mode 1/2/3
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 146.0 x 89.9
- * Weight (g) : 1,070



617505 RF LensUS\$ 4,160.00

Canon RF70-200mm f/4L IS II USM

- * RF Mount for EOS R series mirrorless cameras
- * Angle of View (Diagonal) : 34° ~ 12°
- * Lens Construction: 20 Elements in 15 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 32
- * Image Stabilizer Mode : Mode 1/2/3
- * Filter Diameter (mm) : 72 mm
- * Length x Max. Diameter (mm) : 176.0 x 80
- * Weight (g) : 780



617507 RF LensUS\$ 2,680.40

Canon RF15-35mm f/2.8L IS USM

- * RF Mount for EOS R series mirrorless cameras
- * Angle of View (Diagonal) : 110°30' ~ 63°00'
- * Lens Construction: 16 Elements in 12 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 22
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 82 mm
- * Length x Max. Diameter (mm) : 126.8 x 88.5
- * Weight (g) : 840



617511 RF LensUS\$ 3,592.30

Canon RF14-35mm f/4L IS USM

- * RF Mount for EOS R series mirrorless cameras
- * Angle of View (Diagonal) : 114°00' ~ 63°00'
- * Lens Construction: 16 Elements in 12 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 22
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 99.8 x 84.1
- * Weight (g) : 540



617515 RF LensUS\$ 2,508.40

Canon RF-S 18-45mm f/4.5-6.3 IS USM

- * RF Mount
- * Angle of View (Diagonal) : 74°20' - 10°25'
- * Lens Construction: 17 Elements in 13 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : 22-40
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 49 mm
- * Length x Max. Diameter (mm) : 44.3 x 69.0
- * Weight (g) : 130



618725 RF-S LensUS\$ 512.70

Canon RF100-400mm f/5.6-8 IS USM

- * RF Mount for EOS R series mirrorless cameras
- * Angle of View (Diagonal) : 24°-6°10'
- * Lens Construction: 12 Elements in 9 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 32-45
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 67 mm
- * Length x Max. Diameter (mm) : 164.7 x 79.5
- * Weight (g) : 635



617508 RF LensUS\$ 994.40

Canon RF100-500mm f/4.5-7.1L IS USM

- * RF Mount
- * Angle of View (Diagonal) : 24°- 5°
- * Lens Construction: 02 Elements in 14 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 32-54
- * Image Stabilizer Mode : Mode 1/2/3
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 207.6 x Ø93.8
- * Weight (g) : 1,370



617510 RF LensUS\$4,418.10

Canon RF-S 18-150mm f/3.5-6.3 IS USM

- * RF Mount
- * Angle of View (Diagonal) : 74°20' - 33°40'
- * Lens Construction: 7 Elements in 7 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : 22-32
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 55 mm
- * Length x Max. Diameter (mm) : 84.5 x 69.0
- * Weight (g) : 310



618726 RF-S LensUS\$ 805.20

Canon RF24-240mm f/4-6.3 IS USM

- * RF Mount for EOS R series mirrorless cameras
- * Angle of View (Diagonal) : 84° ~ 10°20'
- * Lens Construction: 21 Elements in 15 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : 22-36
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 72 mm
- * Length x Max. Diameter (mm) : 122.5 x 80.4
- * Weight (g) : 750



#617506 RF LensUS\$ 1,338.50

Canon RF50mm f/1.2L USM

- * RF Mount for EOS R series mirrorless cameras
- * Angle of View (Diagonal) : 46°
- * Lens Construction: 15 Elements in 9 Group
- * No. of Diaphragm Blades : 10
- * Minimum Aperture : 16
- * Image Stabilizer Mode : -
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 108 x 89.8
- * Weight (g) : 950



617499 RF LensUS\$ 3,609.50

Canon RF35mm f/1.8 MACRO IS STM

- * RF Mount for EOS R series mirrorless cameras
- * Angle of View (Diagonal) : 63°
- * Lens Construction: 11 Elements in 9 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 22
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 52 mm
- * Length x Max. Diameter (mm) : 62.8 x 74.4
- * Weight (g) : 305



617500 RF LensUS\$ 770.70

EOS R7

ADS-C
MIRRORLESS CAMERA



Up to 30
Frames
Per Sec

IN-BODY
IMAGE
STABILIZER

EOS iTR
AF X

4K




Canon RF Wide Angle Lens

Canon RF Wide Angle Lens

Canon RF12mm f/1.8L USM

* RF Mount



618959 RF LensComing

Canon RF16mm f/2.8L STM

- * RF Mount
- * Angle of View (Diagonal) : 108°10'
- * Lens Construction: 9 Elements in 7 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 22
- * Image Stabilizer Mode : -
- * Filter Diameter (mm) : 43 mm
- * Length x Max. Diameter (mm) : 40.2 x 69.2
- * Weight (g) : 165



618960 RF LensUS\$ 426.70

Canon RF24mm f/1.4L USM

* RF-Mount Lens/Full-Frame Format

* Weight (g) :



618962 RF LensComing

Canon RF24mm f/1.8 MACRO IS STM

- * RF-Mount Lens/Full-Frame Format
- * Aperture Range: f/1.8 to f/22
- * One UD Element,
- * One Aspherical Element Super Spectra Coating
- * STM Stepping AF Motor
- * 1:2 Max. Magnification, 5.5" Min. Focus
- * Optical Image Stabilizer
- * Customizable Control Ring
- * Weight (g) : 270




618915 RF LensUS\$ 856.80

Canon RF28mm f/1.4L USM

* RF-Mount Lens/Full-Frame Format

* Weight (g) :



618964 RF LensComing

Canon RF28mm f/2.8 Pancake

- * RF Mount / Full-Frame
- * f/2.8 to f/22
- * Gear-Type STM AF Motor
- * Super Spectra Coating
- * Three Aspherical Elements
- * AF/MF Control Switch
- * Full-Time Manual Focus Capability
- * Rounded 7-Blade Diaphragm
- * Weight (g) : 120



618965 RF LensComing

Canon RF35mm f/1.8 MACRO IS STM

- * RF Mount for EOS R series mirrorless cameras
- * Angle of View (Diagonal) : 63°
- * Lens Construction: 11 Elements in 9 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 22
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 52 mm
- * Length x Max. Diameter (mm) : 62.8 x 74.4
- * Weight (g) : 305



618916 RF LensUS\$ 736.30

Canon Standard & Medium Prime Lenses

RF Lens



Canon RF50mm f/1.8 STM

- * RF Mount
- * Angle of View (Diagonal) : 46°00'
- * Lens Construction: 6 Elements in 5 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : 22
- * Image Stabilizer Mode : -
- * Filter Diameter (mm) : 43 mm
- * Length x Max. Diameter (mm) : 40.5 x 69.2
- * Weight (g) : 160



618970 RF LensUS\$ 306.20

Canon RF50mm f/1.2L USM

- * RF Mount for EOS R series mirrorless cameras
- * Angle of View (Diagonal) : 46°
- * Lens Construction: 15 Elements in 9 Group
- * No. of Diaphragm Blades : 10
- * Minimum Aperture : 16
- * Image Stabilizer Mode : -
- * Filter Diameter (mm) : 77 mm
- * Length x Max. Diameter (mm) : 108 x 89.8
- * Weight (g) : 950



618971 RF LensUS\$ 3,609.50

Canon RF85mm f/2 Macro IS STM

- * RF Mount for EOS R series mirrorless cameras
- * Angle of View (Diagonal) : 28°30'
- * Lens Construction: 13 Elements in 9 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 16
- * Image Stabilizer Mode : -
- * Filter Diameter (mm) : 82 mm
- * Length x Max. Diameter (mm) : 117.3 x 103.2
- * Weight (g) : 1195



618973 RF LensUS\$ 891.20

Canon RF85mm f/1.2L USM DS

- * RF Mount for EOS R series mirrorless camera
- * Angle of View (Diagonal) : 28°30'
- * Lens Construction: 13 Elements in 9 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 16
- * Image Stabilizer Mode : -
- * Filter Diameter (mm) : 82 mm
- * Length x Max. Diameter (mm) : 117.3 x 103.2
- * Weight (g) : 1195



618974 RF LensUS\$ 4,831.00

Canon RF85mm f/1.2L USM

- * RF Mount for EOS R series mirrorless cameras
- * Angle of View (Diagonal) : 28°30'
- * Lens Construction: 13 Elements in 9 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 16
- * Image Stabilizer Mode : -
- * Filter Diameter (mm) : 82 mm
- * Length x Max. Diameter (mm) : 117.3 x 103.2
- * Weight (g) : 1195



618975 RF LensUS\$ 4,177.20

Canon RF100mm f/2.8L Macro IS USM

- * RF Mount
- * Angle of View (Diagonal) : 24°00'
- * Lens Construction: 15 Elements in 12 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 32
- * Image Stabilizer Mode : -
- * Filter Diameter (mm) : 67 mm
- * Length x Max. Diameter (mm) : 123 x 77.7
- * Weight (g) : 625



618918 RF LensUS\$ 1,854.60

Canon RF 5.2mm f/2.8L Dual Fisheye 3D VR Lens

- * RF Mount
- * Angle of View (Diagonal) : 190°
- * Lens Construction: 12 Elements in 10 Group
- * Aperture Range: f/2.8 to f/16
- * Captures Stereoscopic 3D 180° VR imagery
- * Two Ultra-Low Dispersion Elements
- * Super-Spectra & Sub-Wavelength Coatings
- * Weather-Sealed Construction
- * Weight (g) : 350



618744 RF LensUS\$ 3,213.80

Canon RF Super Telephoto Lenses



Super Telephoto



Canon RF400mm f/2.8L IS USM

- * RF Mount
- * Angle of View (Diagonal) : 6°10'
- * Lens Construction: 17 Elements in 13 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 32
- * Image Stabilizer Mode : Mode 1/2/3
- * Filter Diameter (mm) : 52mm (Drop-in)
- * Length x Max. Diameter (mm) : 367 x 163
- * Weight (g) : 2890



618982 RF LensUS\$ 17,992.30

Canon RF600mm f/4L IS STM

- * RF Mount
- * Angle of View (Diagonal) : 4°10'
- * Lens Construction: 17 Elements in 13 Group
- * Minimum Aperture : f/32 fixed aperture
- * Image Stabilizer Mode : 5.5-stop
- * Filter Diameter (mm) : 52mm (Drop-in)
- * Length x Max. Diameter (mm) : 472 x 168
- * Weight (g) : 3090



618984 RF LensUS\$ 17,355.70

Canon RF600mm f/11 IS STM

- * RF Mount
- * Angle of View (Diagonal) : 4°10'
- * Lens Construction: 10 Elements in 7 Group
- * Minimum Aperture : f/11 fixed aperture
- * Image Stabilizer Mode : 5-stop
- * Filter Diameter (mm) : 82mm
- * Length x Max. Diameter (mm) : (retracted) 199.5 / 269.5 (shooting) x 93
- * Weight (g) : 930



618985 RF LensUS\$ 1,200.90

Canon RF800mm f/5.6L IS USM

- * RF Mount
- * Angle of View (Diagonal) : 03°05'
- * Lens Construction: 26 Elements in 18 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 64
- * Image Stabilizer Mode : Mode 1/2/3
- * Filter Diameter (mm) : 52mm (Drop-in)
- * Length x Max. Diameter (mm) : 432 x Ø163
- * Weight (g) : 3140



618986 RF LensUS\$ 25,957.80

Canon RF800mm f/11 IS STM

- * RF Mount
- * Angle of View (Diagonal) : 03°05'
- * Lens Construction: 11 Elements in 8 Group
- * Minimum Aperture : f/11 fixed aperture
- * Image Stabilizer Mode : 4-stop
- * Filter Diameter (mm) : 95mm
- * Length x Max. Diameter (mm) : (retracted) 281.8 / 351.8 (shooting) x 101.6
- * Weight (g) : 1260



618987 RF LensUS\$ 1,527.70

Canon RF1200mm f/8L IS USM

- * RF Mount
- * Angle of View (Diagonal) : 02°05'
- * Lens Construction: 26 Elements in 18 Group
- * No. of Diaphragm Blades : 9
- * Minimum Aperture : 64
- * Image Stabilizer Mode : Mode 1/2/3
- * Filter Diameter (mm) : 52mm (Drop-in)
- * Length x Max. Diameter (mm) : 537 x 168
- * Weight (g) : 3340



618988 RF LensUS\$ 30,603.00



RF

RF800mm f/5.6L IS USM
RF1200mm f/8L IS USM



Canon EF-M Lenses & Adapter

Canon Extender, Adapters

Canon Extension, Mounts & Adapters

Canon EF-M Lenses



Canon EF-M 11-22mm f/4-5.6 IS STM

- * EF-M Mount Lens/APS-C Format
- * Angle of View (Diagonal) : 102°10'~63°30'
- * Lens Construction: 12 Elements in 9 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : f/22-f/32
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 55 mm
- * Length x Max. Diameter (mm) : 58.2 x 60.9
- * Weight (g) : 220



612042 EF-M LensUS\$ 512.70

Canon EF-M 55-200mm f/4.5-6.3 IS STM

- * EF-M Mount Lens/APS-C Format
- * Angle of View (Diagonal) : 27°50'~7°50'
- * Lens Construction: 17 Elements in 11 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : f/22-32
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 52 mm
- * Length x Max. Diameter (mm) : 86.5 x 60.9
- * Weight (g) : 260



612045 EF-M Lens (Silver)US\$ 495.50
612052 EF-M Lens (Graphite)\$ 495.50

Canon EF-M 18-150mm f/4.5-6.3 IS STM

- * EF-M Mount Lens/APS-C Format
- * Angle of View (Diagonal) : 74°20'~10°25'
- * Lens Construction: 17 Elements in 13 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : f/22-40
- * Image Stabilizer Mode : Mode 1/2 (Auto)
- * Filter Diameter (mm) : 55 mm
- * Length x Max. Diameter (mm) : 86.5 x 60.9
- * Weight (g) : 300



612051 EF-M LensUS\$ 753.50

Canon EF-M 22mm f/2 STM

- * EF-M Mount Lens/APS-C Format
- * Angle of View (Diagonal) : 63°30'
- * Lens Construction: 7 Elements in 6 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : f/22
- * Filter Diameter (mm) : 43 mm
- * Length x Max. Diameter (mm) : 23.7 x 60.9
- * Weight (g) : 105



612047 EF-M Lens (Silver)US\$ 323.40
612049 EF-M Lens (Graphite)\$ 323.40

Canon EF-M 28mm f/3.5 Macro IS STM

- * EF-M Mount Lens/APS-C Format
- * Angle of View (Diagonal) : 51°55'
- * Lens Construction: 11 Elements in 10 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : f/3.5
- * Image Stabilizer Mode : -
- * Filter Diameter (mm) : 43 mm
- * Length x Max. Diameter (mm) : 60.9 x 45.5
- * Weight (g) : 130



612046 EF-M LensUS\$ 426.70

Canon EF-M 32mm f/1.4 STM Lens

- * EF-M Mount Lens/APS-C Format
- * Angle of View (Diagonal) : 46°10'
- * Lens Construction: 14 Elements in 8 Group
- * No. of Diaphragm Blades : 7
- * Minimum Aperture : 16
- * Image Stabilizer Mode : -
- * Filter Diameter (mm) : 43 mm
- * Length x Max. Diameter (mm) : 56.5 x 60.9
- * Weight (g) : 235



612050 EF-M LensUS\$ 684.70

Canon Mount Adapter EF-EOS M

- * Mount Canon EF/EF-S Lens On EOS-M Camera
- * Compatible with All Lens Functions
- * Detachable Tripod Adapter
- * Camera Cover RF-3, EB Lens Dust Cap



612048 EF-M AddapterUS\$ 168.60



Canon Extender EF 1.4X III

- * EF Mount Teleconverter
- * 1.4x Magnification Factor
- * Microcomputer Controlled
- * Communication Between Lens & Camera
- * Spectra Coating Reduces Ghosting/ Flare
- * Protective Fluorine Coating
- * Dust and Water Resistant
- * Compatible with Select EF Mount Lenses



603400 ExtenderUS\$ 615.90

Canon Extender EF 2.0X III

- * EF Mount Teleconverter
- * 2.0x Magnification Factor
- * Microcomputer Controlled
- * Communication Between Lens & Camera
- * Spectra Coating Reduces Ghosting/ Flare
- * Protective Fluorine Coating
- * Dust and Water Resistant
- * Compatible with Select EF Mount Lenses



603402 ExtenderUS\$ 615.90

Canon Extender RF 1.4x

- * RF mount
- * 1.4x Magnification Factor
- * 7 Elements in 4 Groups
- * Communication Between Lens & Camera
- * Dust and Water Resistance
- * Length x Diameter (mm) : 20.3 x 71.2
- * Weight (g) : 225



603401 ExtenderUS\$ 753.50

Canon Extender RF 2x

- * RF mount
- * 1.4x Magnification Factor
- * 9 Elements in 5 Groups
- * Communication Between Lens & Camera
- * Dust and Water Resistance
- * Length x Diameter (mm) : 39.3 x 71.2
- * Weight (g) : 340



603403 ExtenderUS\$ 891.20

Canon Extension tube



Canon Extension Tube EF 12 II Extension tube

- * EF Mount Teleconverter
- * 1.4x Magnification Factor
- * Microcomputer Controlled
- * Communication Between Lens & Camera
- * Spectra Coating Reduces Ghosting/ Flare
- * Protective Fluorine Coating
- * Dust and Water Resistant
- * Compatible with Select EF Mount Lenses



603406 ExtenderUS\$ 101.50

Canon Extension Tube EF 25 II Extension tube

- * EF Mount Teleconverter
- * 1.4x Magnification Factor
- * Microcomputer Controlled
- * Communication Between Lens & Camera
- * Spectra Coating Reduces Ghosting/ Flare
- * Protective Fluorine Coating
- * Dust and Water Resistant
- * Compatible with Select EF Mount Lenses



603407 ExtenderUS\$ 206.50

Adapter EF/EF-S Lens to EOS R Camera



Canon Control Ring Mount Adapter EF-EOS R

- * Canon EF/EF-S Lens to EOS R Camera
- * Maintains AF and Image Stabilization
- * Configurable Control Ring
- * Dust- and Water-Resistant



Canon Mount Adapter EF-EOS R with Control Ring
617516US\$ 289.00



Canon Mount Adapter EF-EOS R

- * Canon EF/EF-S Lens to EOS R Camera
- * Maintains AF and Image Stabilization
- * Dust- and Water-Resistant



Canon Mount Adapter EF-EOS R - Standard
617517US\$ 151.40

Canon Drop-In Filter Mount Adapter EF-EOS R

- * Canon EF/EF-S Lens to EOS R Camera
- * Maintains AF and Image Stabilization
- * Dust- and Water-Resistant



Canon Mount Adapter EF-EOS R with Circular Polarizer Filter
617518US\$ 355.60

Canon Mount Adapter EF-EOS R with Variable ND Filter
617519\$ 470.20